

# E-Dimming LED Driver

Design and Quality EASEIC of USA

# LPD-30-30A

E-Dimming 0/1-10V DRIVER

SPEC SHEET



30W 30V 1.05A 0/1-10V Dim  
LPD-30-30A  
69203001



**SELV IP67 RoHS**


## Features

- Universal AC input (90~305Vac)
- Designed for LED lighting applications
- IP67/IP65 design for indoor or outdoor installations
- Built-in 3 in 1 dimming function(0/1-10V,PWM or Resistance)
- These drivers operate to specification under wide temperature and electrical ranges to ensure reliability
- LPD series LED drivers for use in Class I, Division 2 hazardous location luminaires
- Cooling by free air convection
- Suitable for dry, damp, and wet location
- 5 year warranty

## Benefits

- Applies to all indoor and outdoor LED lighting
- Helps to maximize energy savings and allows application specific light levels
- Supports majority of available dimming solutions

## Wire Diagram



### Note:

Install in accordance with National and Local Electrical Codes.

Please pay special attention to wiring installation guidelines,

Wrong wiring will cause damage to the LED driver.

Before connection the power, make sure you have access to the LED load.

## Product Data

Input Voltage (Vac)	Output Power (W)	Output Voltage (V)	Output Current (A)	Efficiency @Max Load and 70°C case	Max Case Temp. (°C)	Input Current (Arms)	Max Input Power (W)	THD @Max Load (%)	Power Factor @Max Load	Weight (Lbs/kgs)	Envir. Protection Rating
120	30	20-30	1.05	83.0	Life-75°C UL-85°C	0.32	38.4	<20%	>0.95	1.43/0.65	UL damp and dry
230				84.0		0.16		<20%			
277				85.0		0.13		<20%			

# LPD-30-30A

## E-Dimming 0/1-10V DRIVER

### SPEC SHEET

#### Electrical Specifications

<b>Ordering Information</b>			
Type	LPD-30-30A		
Order Code	69203001		
Full product name	E-Dimming 30W 30V 1.05A 0/1-10V Dim		
<b>Input Information</b>			
Line Voltage	100-277Vac_rms		
Line Current	0.32A@120VAC	0.16A@230VAC	0.13A@277VAC
Line Frequency	50/60Hz		
Min, Mains Voltage operational	90[ <i>min</i> ]		
Max, Mains Voltage operational	305[ <i>max</i> ]		
THD(total)	<20%		
Power Factor(PF)	>0.95		
Inrush Current(Typ.)	Cold Start 50A(twidth=270us measured at 50% Ipeak) at 230VAC		
Leakage Current(Typ.)	<0.75mA/230VAC		
<b>Output Information</b>			
Output voltage	20V to 30V		
Output Constant Current	1.05A		
Maximum open circuit voltage	<60V		
Output Current Ripple (ripple=peak to peak)	2% of nominal output voltage (whichever is greater),measured at 20Mhz bandwidth with 0.1uf ceramic capacitor in parallel with 10uf electrolytic capacitor connected at the end of the output connector.		
Protections	Over Current, Over Voltage, Short Circuit and Open Circuit Protection for LED+ and LED-		
Ambient Temp Range	-40°C to +70°C, 20-95% RH non-condensing		
Max Case Temperature(Tc)	75°C for Life & 85°C for UL Safety		
<b>Features</b>			
Dimming Interface	0-10V(1-10V) Dimming 10V PWM Signal Dimming Resistance Dimming		
0-10V Dimming Specifications	250uA source current form driver, See dim curve for detail.		
10V PWM Signal	100Hz-3KHz PWM		
Resistance Dimming	100Kohm variable resistance		
Dimming range	10-100%		
<b>Environment &amp; Approbation</b>			
Environmental Protection Rating	UL damp and dry		
Agency Approbations	UL8750,UL1310, CSA-C22.2 No.250.0-08,ENEC EN61347-1,EN61347-2-13 independent, EN62384, TUV EN60950-1		
Electromagnetic Compliance	FCC Title 47 Part 15 Class A Compliance to EN55015,EN61000-3-2 Class C(@100% Load);en6100-3-3 Compliance to EN61000-4-2,3,4,5,6,8,11;EN61547,EN55024, light industry level(surge 2KV), criteria A		
Audible noise	<24dB Class A		

All the specifications are typical and at 25 °C Tcase unless specified otherwise


# LPD-30-30A

## E-Dimming 0/1-10V DRIVER

### SPEC SHEET

#### Mechanical Specifications

#### Mechanical Drawing



#### Dimensions

	In.	mm
Case Length(L)	6	154
Case Width(W)	1.6	40
Case Height(H)	1.1	28
Mounting Holes(I1)	5.2	133
Mounting Holes(I2)	1.0	31
Mounting Holes(I3)	0.18	4.5
Mounting Holes(I4)	5.7	146
Input Wire(Wire1) SJTW 18AWG x 3C	11.8	300 ± 20
Output Wire(Wire2) SJTW 2x18 AWG x 2C	11.8	300 ± 20
Overall Length	6	154

**EASEIC**

© Copyright 2013 EASEIC INC.  
All rights reserved. Rev A1.0  
Data is subject to change without notice.  
www.easeic.com

#### Easeic Inc.

27 Hall Street, Brooklyn, NY 11205  
Tel.: 1-718-243-9388  
Fax: 1-718-243-9403  
Customer Support  
Customer Care: 1-646-4029788  
E-Mail: ny@easeic.com

#### Easeic Asia Limited.

Rm. 19C, Lockhart Ctr., 301-307  
Lockhart Rd., Wan Chai, Hong Kong  
Tel.: 852-6955-8075  
Fax: 852-6915-3639  
E-Mail: info@easeic.com

#### Easeic Sci-tech Co., Ltd.

No. 37 Huancun Xi Rd., Liangtian  
Industrial Area,  
Baiyuan District, Guangzhou, China  
Tel.: 86-20-8230-9676  
Fax: 86-20-8230-9677  
E-Mail: sales@easeic.com